




N-type i-TOPCon

BIFACIAL DUAL GLASS MONOCRYSTALLINE MODULE

TSM-NEG18RC.27 490-515W

515_W / MAXIMUM
POWER OUTPUT

23.2% / MAXIMUM
EFFICIENCY



High customer value

- Clear black, designed with aesthetics in mind, suitable for residential and C&I rooftop
- Lower LCOE (levelized cost of energy), reduced BOS (balance of system) cost, shorter payback time
- Designed for compatibility with existing mainstream system components
- Easy to handle and install on roofs with excellent size and light weight



High power up to 515W

- Up to 23.2% module efficiency, on 210 innovation platform
- Patented i-TOPCon technology with continuous efficiency improvement, including contact resistance reduction, rear reflection enhancement and edge quality repairment



Dual-glass design, high reliability


- Less prone to micro-cracks and scratches on the back during installation
- Excellent fire rating and weather resistance, proven durability in salt, sand, and ammonia environments.
- Mechanical performance up to 5400 Pa positive load and 2400 Pa negative load



High energy yield

- Excellent low irradiation performance, validated by 3rd party
- Lower temperature coefficient (-0.29%/°C) and operating temperature
- Higher bifaciality, with up to 10%~20% additional power gain from back side depending on albedo

Performance Warranty



* Please refer to product warranty for details

Comprehensive Products and System Certificates

IEC61215/IEC61730/IEC61701/IEC62716

ISO 9001: Quality Management System

ISO 14001: Environmental Management System

ISO14064: Greenhouse Gases Emissions Verification

ISO45001: Occupational Health and Safety Management System



ELECTRICAL DATA (STC & NOCT & BNPI)

Testing Condition	STC	NOCT	BNPI	STC	NOCT	BNPI	STC	NOCT	BNPI	STC	NOCT	BNPI	STC	NOCT	BNPI	STC	NOCT	BNPI
Peak Power Watts- $P_{MAX}(W_p)^*$	490	375	542	495	378	548	500	382	554	505	386	559	510	390	565	515	394	570
Power Selection (W)**	0 ~ +5																	
Maximum Power Voltage- V_{MPP} (V)	32.90	31.00	32.90	33.10	31.30	33.10	33.30	31.50	33.30	33.50	31.80	33.50	33.70	31.90	33.70	33.90	32.20	33.90
Maximum Power Current- I_{MPP} (A)	14.91	12.06	16.47	14.97	12.08	16.55	15.03	12.11	16.63	15.09	12.15	16.68	15.14	12.21	16.77	15.20	12.23	16.83
Open Circuit Voltage- V_{oc} (V)	39.60	37.60	39.60	39.80	37.70	39.80	40.10	38.00	40.10	40.30	38.30	40.30	40.60	38.50	40.60	40.90	38.80	40.90
Short Circuit Current- I_{sc} (A)	15.80	12.74	17.51	15.83	12.76	17.57	15.86	12.78	17.61	15.89	12.81	17.65	15.93	12.84	17.68	15.96	12.86	17.68
Module Efficiency η_m (%)	22.0			22.3			22.5			22.7			22.9			23.2		

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5. NOCT: Irradiance at 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s. BNPI: Irradiance: front 1000W/m², rear 135W/m², Temperature 25°C, Air Mass AM1.5
 *Measuring tolerance: $\pm 3\%$. **Power selection up to: +3%.

Electrical characteristics with different power bin (reference to 5% & 10% backside power gain)

Backside Power Gain	5%	10%	5%	10%	5%	10%	5%	10%	5%	10%	5%	10%
Peak Power Watts- $P_{MAX}(W_p)$	515	539	520	545	525	550	530	556	536	561	541	567
Maximum Power Voltage- V_{MPP} (V)	32.90	32.90	33.10	33.10	33.30	33.30	33.50	33.50	33.70	33.70	33.90	33.90
Maximum Power Current- I_{MPP} (A)	15.66	16.40	15.72	16.47	15.78	16.53	15.84	16.60	15.90	16.65	15.96	16.72
Open Circuit Voltage- V_{oc} (V)	39.60	39.60	39.80	39.80	40.10	40.10	40.30	40.30	40.60	40.60	40.90	40.90
Short Circuit Current- I_{sc} (A)	16.59	17.38	16.62	17.41	16.65	17.45	16.68	17.48	16.73	17.52	16.76	17.56

Power Bifaciality: 80 $\pm$ 5%.

TEMPERATURE RATINGS

NOCT (Nominal Operating Cell Temperature) 43°C ($\pm 2^\circ\text{C}$)

Temperature Coefficient of P_{MAX} -0.29% /°C

Temperature Coefficient of V_{oc} -0.24% /°C

Temperature Coefficient of I_{sc} 0.04% /°C

Due to different testing methods, the actual performances might differ from the declared specifications.

APPLICATION CONDITIONS


Operating Temperature -40~+70°C

Maximum System Voltage 1500V DC (IEC)


Max Series Fuse Rating 30A

CURVES OF PV MODULE

I-V CURVES OF PV MODULE (505W)




P-V CURVES OF PV MODULE (505W)



MECHANICAL DATA

Solar Cells	N-type i-TOPCon Monocrystalline
No. of cells	108 cells
Module Dimensions	1961×1134×30 mm (77.20×44.65×1.18 inches)
Weight	23.5 kg (51.8 lb)
Front Glass	1.6mm (0.06inches), AR Coating Heat Strengthened Glass
Back Glass	1.6mm (0.06inches), Heat Strengthened Glass
Frame	30mm (1.18inches) Anodized Aluminium Alloy, Black
J-Box	IP 68 rated
Cables	Photovoltaic Technology Cable 4.0mm ² (0.006 inches ²) Portrait: 200/320 mm (7.87/12.60 inches) Length can be customized
Connector	TS4 Plus / TS4 / MC4 EV02*
Packaging	Modules per box: 36 pieces Modules per 40' container: 864 pieces

*The connector names listed are general names; specific types are subject to the certification documents.



www.trinasolar.com

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.
 © 2025 Trina Solar Co., Ltd. All rights reserved. Specifications included in this datasheet are subject to change without notice.
 The right of final interpretation belongs to Trina Solar Co., Ltd.
 Version number: TSM_EN_2025_A